




# Sonnenschein 6V 1 OGiV 18 – A706/21 data sheet



## Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Switch to: Discharge at 25 °C/inches/lb

Exide type designation	Type acc. to DIN 40 741	Nom. Voltage V	Nom. capacity C <sub>10</sub> 1.80 Vpc 20°C Ah	Length (l) max. mm	Installed length B/L mm	Width (b/w) max. mm	Height top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A706/21	6V 1 OGiV 18	6	21.0	115	125	178	241	268	8.50	16.8	367	F-M5

## Constant-current discharge in A @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h	8 h	10 h
NGA7060021HS0FA	1.80	36.3	31.3	26.4	23.1	18.9	11.5	7.30	5.50	3.70	2.60	2.10
NGA7060021HS0FA	1.77	40.2	34.2	28.0	24.2	19.3	11.9	7.30	5.50	3.80	2.60	2.10
NGA7060021HS0FA	1.75	42.8	36.1	29.0	25.0	19.6	12.1	7.30	5.50	3.80	2.60	2.10
NGA7060021HS0FA	1.70	48.0	39.0	31.0	26.5	20.4	12.1	7.40	5.50	3.80	2.60	2.10
NGA7060021HS0FA	1.65	52.0	41.0	32.5	26.9	20.4	12.2	7.40	5.60	3.80	2.60	2.10
NGA7060021HS0FA	1.60	55.0	42.5	33.2	26.9	20.5	12.2	7.40	5.60	3.80	2.60	2.10

## Constant-power discharge in W/block @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h
NGA7060021HS0FA	1.80	186	157	137	121	97.0	65.0	41.0	31.0	21.0
NGA7060021HS0FA	1.77	199	165	144	126	100	66.0	42.0	31.0	21.0
NGA7060021HS0FA	1.75	212	173	151	131	103	67.0	42.0	32.0	21.0
NGA7060021HS0FA	1.70	230	189	159	137	106	68.0	43.0	32.0	22.0
NGA7060021HS0FA	1.65	251	202	164	141	108	68.0	43.0	32.0	22.0
NGA7060021HS0FA	1.60	266	210	168	143	109	68.0	43.0	32.0	22.0

© 2000 – 2010 Exide Technologies. All rights reserved. Subject to alterations. [Click here for legal notice.](#)

