


Sonnenschein 6V 3 OGiV 54 – A706/63 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Switch to: Discharge at 25 °C/inches/lb

Exide type designation	Type acc. to DIN 40 741	Nom. Voltage V	Nom. capacity C ₁₀ 1.80 Vpc 20°C Ah	Length (l) max. mm	Installed length B/L mm	Width (b/w) max. mm	Height top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A706/63	6V 3 OGiV 54	6	63.0	198	208	178	241	272	16.3	5.8	1058	F-M6

Constant-current discharge in A @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h	8 h	10 h
NGA7060063HS0FB	1.80	108	93.9	79.2	69.3	56.7	34.5	21.9	16.5	11.1	7.70	6.30
NGA7060063HS0FB	1.77	120	102	83.9	72.7	58.0	35.6	21.9	16.5	11.3	7.70	6.30
NGA7060063HS0FB	1.75	128	108	87.0	75.0	58.8	36.6	21.9	16.5	11.3	7.70	6.30
NGA7060063HS0FB	1.70	144	117	93.0	79.5	61.2	36.6	22.2	16.5	11.4	7.70	6.30
NGA7060063HS0FB	1.65	156	123	97.5	80.7	61.2	36.6	22.2	16.9	11.4	7.70	6.30
NGA7060063HS0FB	1.60	165	127	99.6	80.7	61.5	36.6	22.2	16.9	11.4	7.70	6.30

Constant-power discharge in W/block @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h
NGA7060063HS0FB	1.80	558	472	411	362	292	194	123	93.0	63.0
NGA7060063HS0FB	1.77	596	496	432	377	300	197	125	93.0	63.0
NGA7060063HS0FB	1.75	635	520	452	393	309	200	126	96.0	63.0
NGA7060063HS0FB	1.70	689	568	477	412	319	203	129	96.0	65.0
NGA7060063HS0FB	1.65	753	605	492	423	324	204	129	96.0	65.0
NGA7060063HS0FB	1.60	798	630	503	429	326	205	129	96.0	66.0